

CLAIMS:

1. A method of determining if a received data sequence is a Barker spreaded sequence, the method comprising the steps of correlating said received data sequence, performing a filtering operation to create a data set consisting of the sum of the correlation result of K subsequent data bits, where K is a quality parameter and comprises an integer
 5 greater than 1, deriving a parameter L by determining the difference between a maximal correlation result and a minimal correlation result normalized by the minimal correlation result, and comparing the parameter L with a predetermined threshold value to determine if said received signal is a Barker spreaded sequence.

10 2. A method according to claim 1, wherein the step of correlating the received sequence comprises deriving a signal $y(kT + n)$ using the formula:

$$y(kT + n) = \sum_{i=0}^{T-1} b_i^* r(kT + n - i)$$

where b_i^* is the equivalent complex conjugated Barker sequence, $r(kT + n)$ is a sampled received data sequence, $k = 0, 1, \dots$, and T is the sampling rate at which the
 15 received sequence is sampled prior to application thereof to the correlator.

3. A method according to claim 1 or claim 2, wherein the magnitude of $y(kT + n)$ is obtained prior to the step of performing the filtering operation.

20 4. A method according to any one of the preceding claims, wherein the filtering operation comprises the calculation of a running average of the correlation results, using the formula:

$$\hat{s}_K(n) = \frac{1}{K} \sum_{l=1}^K s(lT + n), \text{ for } n = 0, \dots, T - 1$$

25 5. A method according to any one of the preceding claims, wherein L is calculated using the formula:

$$L = \frac{\max_{n \leq K} \hat{\rho}(n) - \min_{n \leq K} \hat{\rho}(n)}{\min_{n \leq K} \hat{\rho}(n)}$$

and a decision signal indicating the presence of a Barker sequence is output if $L > T$, and a decision indicating no Barker sequence is output otherwise, where T is a predetermined threshold value.

5

6. Apparatus for determining if a received data sequence is a Barker spreaded sequence, the apparatus comprises a correlator (12) arranged to correlate said received data sequence, a filter (16) arranged to perform a filtering operation to create a data set consisting of the sum of the correlation result of K subsequent data bits, where K is a quality parameter and comprises an integer greater than 1, a calculator (20) arranged to derive a parameter L by determining the difference between a maximal correlation result and a minimal correlation result normalized by the minimal correlation result, and a comparator (22) arranged to compare the parameter L with a predetermined threshold value to determine if said received signal is a Barker spreaded sequence.

15

7. A decoder comprising an apparatus according to claim 6.

8. A receiver comprising a decoder according to claim 7.

- 20 9. Apparatus arranged to determine if a received data sequence is a Barker spreaded sequence by using the method of claim 1.

10. Decoder comprising an apparatus according to claim 9.

- 25 11. Receiver comprising a decoder according to claim 10.

12. A wireless local area network comprising at least one transmitter and at least one receiver according to claim 8 or 11.